



Two-way, high-power full-range system for active or passive operation

- 15” Low Frequency transducer.
- 3” titanium compression driver with 1.4”-throat diameter.
- Rotatable CAD optimized horn.
- Very linear frequency response from 50 Hz to 20 kHz
- Bi-amp or passive operation
- integrated crossover with an acoustic crossover frequency of 1500 Hz
- 4th order crossover network
- Voice coli tracking protection circuits.
- compact, trapezoidal-shaped,
- 13-ply birch plywood
- optional flying hardware
- Input NL4
- Easy external operation mode selection switch
- Black textured paint
- Galvanneal front grill with acoustic foam front

Technical specifications:

| | |
|--|-------------------------|
| Frequency response (-10dB): | 50 Hz – 20Khz |
| Frequency response with power H and RCM 26 | 40 Hz – 20Khz |
| Nominal coverage H | 90° - rotatable |
| Nominal coverage V | 45° - rotatable |
| Crossover Frequency | 1500 Hz |
| Axial Sensitivity (1W/1Mtr) | 100 dB |
| Maximum Calc. SPL | 133 dB |
| Power Handling | 500 W Cont / 2000W Peak |
| Voice coli tracking | Yes |
| Nominal impedance | 8 Ohms |
| Connectors | NL4 |
| Dimensions | 441 x 780 x 407 mm |
| Weight | max. 26 kg |

Make: Dynacord or equivalent

Type: VL 152

Delivery and mounting ready for operation

Make offered:

Type:

[Type text]